



LOUDSPEAKER COMPARISON TABLE

[SEPTEMBER 2012]

FLOOR-STANDING / LARGE FORMAT	DOMINANCE	DEFINITION	DRUID	OMEN DEF
Mark [Revision]	Mk.I [Rev. A]	Mk.IV [Rev. A]	Mk.V [Rev. A]	Mk.I [Rev. B]
Recent Update	price increase			-NEW-
Price Int.* (USD) Standard Finishes	86,000 /pr	16,995 /pr	6,995 /pr	4,295 /pr
Type & Form	2-ch. stereo floorstanding (extra large)	2-ch. stereo floorstanding (large)	2-ch. stereo floorstanding (large)	2-ch. stereo floorstanding (large)
Efficiency (1W@1m dB SPL)	101	101	101	100
Impedance Nominal (Z Ω)	6	8*	16	8*
Bandwidth (Hz)	12-20,000	16-20,000	35-20,000	32-25,000
Typical Input Power Range (W)	1-12	2-24	2-24	2-24
Maximum Music Input Power (W)	600	500	200	400
Amplification Notes	requires signal processing	no bridged main amps w/o isolation x-former	amps that prefer high-efficiency, high-resolution, higher impedance speakers	amp omnifarious
Amp Configurations	bi-amp or tri-amp	standard with integrated sub amp	standard	standard
Cable Connection	Cardas™ single knob binding posts	ZuB3™ + spades via adaptor C13/C14 mains	ZuB3™ + CE 5-way posts	CE 5-way posts
ideal seated listening window	8-20' [2.5-6m]	7-40' [2-12m]	3' [1m+]	7-40' [2-12m]
listening room size	large-huge	medium-huge	small-huge	medium-huge
footprint height x width x depth (centimeters)	62 x 16 x 21" [158 x 40.7 x 53.4]	50 x 12.75 x 12.75" [125 x 32.4 x 32.4]	50 x 12.75 x 12.75" [125 x 32.4 x 32.4]	47 x 12 x 12" [119.4 x 30.5 x 30.5]
product weight each	350# [159kg]	150# [68kg]	80# [36 kg]	78# [35 kg]
driver compliment	Zu103ND/G1-16 (x3) full-range drivers Radian 850 based tweeters (x2) 15" sub-subwoofer	Zu103ND/G1-16 (x2) full-range drivers Radian 850 based tweeter LAB-12 subwoofer	Zu103ND/G1-16 full-range driver Radian 850 based tweeter	Zu103ND/G1-16 (x2) full-range drivers Zu/U-APT-L2 tweeter
electroacoustic loading model	Zu-Griewe™	Zu-Griewe™	Zu-Griewe™	Zu-Griewe™
driver array technology	Dominance array™	Definition array™	1-1/2 way	Definition array™
acoustic handoff points	30 / 10,000	40 / 10,000	8,000	10,000
cabinet material	mixed materials	mixed materials	mixed materials	comp-60
stereo pair match tolerance	.2%	.5%	.5%	1%
internal cable	Event™ cable harness	Event™ cable harness	Event™ cable harness	Mission™ hookup wire
packaging (ASTM & CE compliant)	wood crate	foam encapsulate	foam encapsulate	foam encapsulate
shipping (U.S.A.)	UPS Freight	UPS Freight	UPS Ground	UPS Ground
needed to unpack	piano movers	you and a buddy	just you	just you
warranty (limited)	5-years	5-years / 2-years	5-years	5-years
compliance product	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE

FLOOR STANDING / MEDIUM FORMAT	SOUL SUPREME	SOUL SUPERFLY	SOUL	UNION	OMEN
Mark [Revision]	Mk.I [Rev. A]	Mk.I [Rev. B]	Mk.II [Rev. A]	Mk.I [Rev. A]	Mk.I [Rev. B]
Recent Update	-NEW-		-NEW LOWER PRICE-		-NEW-
Price Int.* (USD) Standard Finishes	\$5,595 /pr	\$4,295 /pr	\$2,995 /pr	\$2,995 /pr	\$2,000 /pr
Type & Form	center or stereo floorstanding (medium-narrowing)	center or stereo floorstanding (medium-narrowing)	center or stereo floorstanding (medium-narrowing)	center or stereo floorstanding (medium)	center or stereo floorstanding (medium)
Efficiency (1W@1m dB SPL)	101	101	99	99	97
Impedance Nominal (Z Ω)	16	16	8	8	12
Bandwidth (Hz)	35-20,000	35-25,000	45-22,000	45-22,000	35-25,000
Typical Input Power Range (W)	2-24	2-24	2-24	2-24	6-36
Maximum Music Input Power (W)	200	200	150	150	200
Amplification Notes	amps that prefer high-efficiency, high-resolution, higher impedance speakers	amps that prefer high-efficiency, high-resolution, higher impedance speakers	amp omnifarious	amp omnifarious	amp omnifarious
Amp Configurations	standard	standard	standard	standard	standard
Cable Connection	ZuB3™ + CE 5-way posts	CE 5-way posts	CE 5-way posts	CE 5-way posts	CE 5-way posts
ideal seated listening window	4-50' [1-15m]	4-50' [1-15m]	2' [.5m+]	2' [.5m+]	3' [1m+]
listening room size	small-large	small-large	very small-large	very small-large	small-large
footprint height x width x depth (centimeters)	38 x 12.2 x 12.2" [96.5 x 30.8 x 24.1]	38 x 12.2 x 12.2" [96.5 x 30.8 x 24.1]	31.5 x 12.2 x 12.2" [80 x 30.8 x 24.1]	36 x 11 x 11" [92 x 30.5 x 30.5]	36 x 12 x 12" [92 x 30.5 x 30.5]
product weight each	70# [32kg]	54# [24kg]	45# [21kg]	46# [21kg]	54# [24kg]
driver compliment	Zu103ND/G1-16 full-range driver Radian 850 based tweeter	Zu103ND/G1-16 full-range driver Zu/U-APT-L2 tweeter	ZuCX/ND-8 full-range co-ax driver 1001 tweeter	ZuCX/ND-8 full-range co-ax driver 1001 tweeter	Zu260FRD/G4 full-range driver Zu/U-APT-L2 tweeter
electroacoustic loading model	Zu-Griewe™	Zu-Griewe™	Zu-Griewe™	Zu-Griewe™	Zu-Griewe™
driver array technology	1-1/2 way	1-1/2 way	1-1/2 way	1-1/2 way coaxial	1-1/2 way
acoustic x-over points	8,000	12,000	12,000	12,000	12,000
cabinet material	comp60+	comp60+	comp60	comp60	comp60
stereo pair match tolerance	.5%	.5%	.5%	.5%	1%
internal cable	Event™ cable harness	Event™ cable harness	Mission™ hookup wire	Mission™ hookup wire	Mission™ hookup wire
packaging (ASTM & CE compliant)	foam encapsulate	foam encapsulate	foam encapsulate	foam encapsulate	foam encapsulate
shipping (U.S.A.)	UPS Ground	UPS Ground	UPS Ground	UPS Ground	UPS Ground
needed to unpack	just you	just you	girlfriend	girlfriend	girlfriend
warranty (limited)	5-years	5-years	5-years	5-years	5-years
compliance product	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE

BOOKSHELF	DEF-HEAD	CUBE	OMEN BOOKSHELF
Mark [Revision]	Mk.I [Rev. A]	Mk.I [Rev. A]	Mk.I [Rev. B]
Recent Update	(secret menu item)	-NEW LOWER PRIC-	-NEW-
Price Int.* (USD) Standard Finishes	\$5,600 /each	\$1,595 /pr	\$1,700 /pr
Type & Form	center or stereo small riser stand mount (medium-short)	bookshelf stand mount	bookshelf stand mount
Efficiency (1W@1m dB-SPL)	101	99	97
Impedance Nominal (Z Ω)	8*	8	12
Bandwidth (Hz)	32-20,000	70-22,000	50-25,000
Typical Input Power Range (W)	2-24	2-24	12-40
Maximum Music Input Power (W)	400	150	200
Amplification Notes	amp omnifarious	amp omnifarious	amp omnifarious
Amp Configurations	standard	standard	standard
Cable Connection	ZuB3™ + CE 5-way posts	CE 5-way posts	CE 5-way posts
ideal seated listening window	7-40' [2-12m]	2' [.5m+]	3' [1m+]
listening room size	medium-huge	very small-large	small-large
footprint height x width x depth (centimeters)	33.5 x 12.75 x 12.75" [85 x 32.4 x 32.4]	10.5 x 10.5 x 10.5" [27 x 27 x 27]	18 x 12 x 12" [46 x 30.5 x 30.5]
product weight each	68# [31kg]	24# [10kg]	35# [16kg]
driver compliment	Zu103ND/G1-16 (x2) full-range driver Radian 850 based tweeter	ZuCX/ND-8 full-range co-ax driver 1001 tweeter	Zu260FRD/G4/ND-12 full-range driver Zu/U-APT-L2 tweeter
electroacoustic loading model	sealed	sealed	sealed
driver array technology	Definition array™	1-1/2 way	1-1/2 way
acoustic x-over points	40 / 10,000	12,000	12,000
cabinet material	mixed materials	comp-60	comp-60
stereo pair match tolerance	0.5%	1%	1%
internal cable	Event™ cable harness	Mission™ hookup wire	Mission™ hookup wire
packaging (ASTM & CE compliant)	foam encapsulate	foam encapsulate	foam encapsulate
shipping (U.S.A.)	UPS Ground	UPS Ground	UPS Ground
needed to unpack	just you	your kids	your kids
warranty (limited)	5-years	5-years	5-years
compliance product	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE

CENTER	DEF-HEAD	DRUID CENTER	OMEN CENTER	CUBE SINGLE
Mark [Revision]	Mk.I [Rev. A]	Mk.V [Rev. A]	Mk.I [Rev. B]	Mk.I [Rev. A]
Special Notes	(secret menu item)	(secret menu item)	-NEW-	-NEW LOWER PRICE-
Price Int.* (USD) Standard Finishes	\$5,600 /each	\$4,500 /each	\$900 /each	\$799 /each
Type & Form	center or stereo floor-standing (medium-short)	center (horizontal)	center (horizontal)	center, stereo, or effects
Efficiency (1W@1m dB SPL)	101	101	97	99
Impedance Nominal (Z Ω)	8*	16	12	8
Bandwidth (Hz)	32-20,000	50-20,000	50-25,000	70-22,000
Typical Input Power Range (W)	2-24	2-24	12-40	2-24
Maximum Music Input Power (W)	400	200	200	150
Amplification Notes	amp omnifarious	amps that prefer high-efficiency, high-resolution loudspeakers	amp omnifarious	amp omnifarious
Amp Configurations	standard	standard	standard	standard
Cable Connection	ZuB3™ + CE 5-way posts	ZuB3 + CE 5-way posts	CE 5-way posts	CE 5-way posts
ideal seated listening window	7-40' [2-12m]	3' [1m+]	3' [1m+]	2' [.5m+]
listening room size	medium-huge	small-huge	small-large	very small-large
footprint height x width x depth (centimeters)	33.5 x 12.75 x 12.75" [85 x 32.4 x 32.4]	11.5 x 26 x 7" [85 x 32.4 x 32.4]	11" x 19-1/2" x 8" [28 x 50 x 20.4]	10.5 x 10.5 x 10.5" [27 x 27 x 27]
product weight each	68# [31kg]	45# [20kg]	31# [14kg]	24# [10kg]
driver compliment	Zu103ND/G1-16 (x2) full-range driver Radian 850 based tweeter	Zu103ND/G1-16 full-range driver Radian 850 based tweeter (x2)	Zu260FRD/G4 full-range driver Zu/U-APT-L2 (x2) tweeter	ZuCX/ND-8 full-range co-ax driver 1001 tweeter
electroacoustic loading model	sealed	sealed	sealed	sealed
driver array technology	Definition array™	Druid Center Array™	1-1/2 way	1-1/2 way
acoustic x-over points	40 / 10,000	8,000	12,000	12,000
cabinet material	mixed materials	mixed materials	comp-60	comp-60
internal cable	Event™ cable harness	Event™ cable harness	Mission™ hookup wire	Mission™ hookup wire
packaging (ASTM & CE compliant)	foam encapsulate	foam encapsulate	foam encapsulate	foam encapsulate
shipping (U.S.A.)	UPS Ground	UPS Ground	UPS Ground	UPS Ground
needed to unpack	just you	just you	your kids	your kids
warranty (limited)	5-years	5-years	5-years	5-years
compliance product	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE	CE RoHS WEEE

* Applicable taxes, duties and freight charges not included.

† Latent 32 ohm impedance possible, internal cabling can be ran series.